



RESIDUAL CURRENT DEVICE 2P 40A 300mA 6kA TYPE AC PR8NM

Code: 500-37010

TECHNICAL DATA

Supply Voltage (V):	230V
Amperage (A):	40A
Operating Frequency (Hz):	50/60Hz
Ingress Protection (IP):	IP20
Operating Temperature °C:	-25°C - +50°C
Product Color:	Λευκό/White
Product Material:	Πλαστικό/ Plastic
Product Net Weight (kg):	0.170
Product Gross Weight (kg):	0.170
Packing (pcs):	6/60
Packaging:	Box with Sticker
Height:	81mm
Width:	35mm
Length:	77.5mm
Guarantee Eurolamp:	2 Χρόνια/ 2 Years
Certifications:	Nau/Yes
CE Mark:	Nau/Yes
Cable Cross Section:	10mm
Surge Protection:	Nau/Yes
Busbar mm (Gacia):	25
Poles (Gacia):	2P
Contact Position Indication (Gacia):	Nau/ Yes
Rated Short Circuit Breaking Capacity (Gacia):	6kA
Breaking Capacity (Gacia):	6kA
mA (Gacia):	300mA



EUROLAMP®

Pioneers in New Technology !

Product Standard (Gacia):	IEC61008-1
Service Life (Gacia):	Μηχανικός: 10000 Ηλεκτρικός: 4000/ Mechanical: 10000 Electrical: 4000
Curve (Gacia):	C
Terminal Connection Type (Gacia):	Καλώδιο, Γέφυρα Χαλκού Τύπου L & U/ Wire, L & U Type Busbar
Residual Current Protection Type (Gacia):	Ηλεκτρομαγνητικός/ Electromagnetic
Residual Current Working Type (Gacia):	AC

