



RESIDUAL CURRENT CIRCUIT BREAKER WITH OVERLOAD PROTECTION 3P+N C 32A 30mA 6kA TYPE A PL8M4

Code: 500-43565

TECHNICAL DATA

Supply Voltage (V):	400V
Amperage (A):	32A
Operating Frequency (Hz):	50/60Hz
Ingress Protection (IP):	IP20
Operating Temperature °C:	-25°C - +65°C
Product Color:	Λευκό/White, Blue handle
Product Material:	PA66
Product Net Weight (kg):	0.426
Product Gross Weight (kg):	0.426
Packing (pcs):	3/30
Packaging:	Box with Sticker
Height:	75mm
Width:	71.6mm
Length:	81mm
Guarantee Eurolamp:	2 Χρόνια/ 2 Years
Certifications:	Ναι/Yes
CE Mark:	Ναι/Yes
Cable Cross Section:	25mm ²
Busbar Type:	U Type
Poles (Gacia):	4
Contact Position Indication (Gacia):	Yes
Rated Short Circuit Breaking Capacity (Gacia):	6kA
Breaking Capacity (Gacia):	6kA
mA (Gacia):	30
Product Standard (Gacia):	IEC61010



EUROLAMP[®]

Pioneers in New Technology !

Service Life (Gacia):	Μηχανικό/ Mechanical: 6000, Ηλεκτρικό/Electrical: 3000
-----------------------	---

Curve (Gacia):	C
----------------	---

Terminal Connection Type (Gacia):	Καλώδιο/Wire
-----------------------------------	--------------

Residual Current Protection Type (Gacia):	A
--	---

